

ICX7450-24P | RUCKUS ICX 7450-24P



Mid-Range Access 24 Ports 1G PoE Switch

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Ethernet switch
Product Brand	RUCKUS®

General Specifications

Switching Capacity, maximum	288 Gb/s
1 GbE RJ45 Ports, quantity, maximum	24
1 GbE SFP Ports, quantity, maximum	4
10 GbE SFP+ Ports, quantity, maximum	12
10 GbE RJ45 Ports, quantity, maximum	12
40 GbE QSFP Ports, quantity, maximum	3
PoE Power Budget, maximum	1500 W
Switches per Stack, maximum	12
Aggregate Stack Bandwidth, maximum	960 Gb/s
PoE/PoE+	Yes
Stacking	Yes
sFlow	Yes
Layer 3 (STATIC, RIP, OSPF)	Yes
OpenFlow with Hybrid Port Mode	Yes
Campus Fabric Technology	Yes
Redundant Power Option	Yes
Hot Swap Internal Power Supplies & Fans	Yes
802.3bt2 (90 W PoE Power per Port)	Yes
VRF	Yes
EEE (Energy Efficient Ethernet)	Yes
IPsec VPN, with service module	Yes

ICX7450-24P | RUCKUS ICX 7450-24P

MACsec	Yes
BGP	Yes
Reversible Airflow Option	Yes
VxLAN	No
Multi Chassis Trunking (MCT)	No

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

